

Print Armor™ Signs Cleaning Procedure:

Light Cleaning:

Cleaning with a soft cloth and soapy, lukewarm water is enough to get rid of organic residues and dust. This cleaning method may be useful before trying to clean a graffiti. Using a common dish soap is effective.

Cleaning Graffiti:

99% isopropyl alcohol* is the only tested and effective solvent that cause no damage for the surface. Any other cleaning product or solvent might damage the Print Armor™ coating.

- Spray with 99% isopropyl alcohol* and let sit for a few seconds.
- Rub with a soft cloth, then wipe.
- Repeat if necessary.

Persistent Graffiti:

- Lay sign down on a flat surface.
- Cover affected area with a dry soft cloth.
- Soak the soft cloth with 99% isopropyl alcohol* and let sit for at least 5 minutes.
- Remove the soaked soft cloth and rub with a second soft cloth.
- To overcome more persistent graffiti, it may be necessary to repeat these steps a few times. It may also be needed to spray more 99% isopropyl alcohol*, let sit, then rub again to allow paint to dissolve.

Persistent Glue:

Stickers should be easily removable with 99% isopropyl alcohol*. However, some glue types may be more persistent. Slight use of lighter fuel (commonly butane)* may do the trick.

- Pour light fuel* on affected area. Let sit for a few seconds.
- Use a plastic scraper at about 15 degrees angle to make sure not to scratch the surface.
- Once all glue is removed, clean the surface with 99% isopropyl alcohol*.



Use only 99% isopropyl alcohol*



Stronger products will damage finish

*See safety precautions and data sheet of each product used.